



LINITOP®

BOUCHE-PORES

Transparent grain filler



INTERIOR

priority to wood

Description	Transparent grain filler for interior woodwork. Product ready to use.
Classification	Family 1 - Class 4a (according to classifications NBT 22-003 and NFT 36-005).
Properties	<ul style="list-style-type: none"> • Fills small surface imperfections before application of the top varnish. • Never apply directly to the bare wood but only after a first coat of Linitop Vernis*. • Only recoatable with an alkyd-resin based varnish. • Highly filling. Can be applied to old varnish in a good condition. • Easy sanding. • Very good brushability.
Basic uses	Applicable to resinous woods, broadleaved woods and tropical hardwoods, indoors.
Characteristics	<ul style="list-style-type: none"> • Composition: Urethane alkyd resins. • Density (at +20°C): 0.925 ± 0.05. • Flash point: > 60°C. • Viscosity: Semi-fluid thick liquid. • Solid content: 58% ± 3. • VOC: EU limit value for this product (cat A/e): 400 g/l (2010). This product contains a maximum of 400 g/l VOC. • Packaging: 0.75 l and 2.5 l. • Shelf life: At least 2 years in the unused closed original packaging. Close the packaging well after use. • Storage conditions: Keep away from frost and high temperatures. • Appearance in the can: Translucent milky liquid. • Appearance of the dry product: Semi-gloss and transparent. • Tools: Brush. • Dilution: Ready to use. • Cleaning of the tools: White spirit. • Conditions of application: Respect the conditions and instructions stipulated by the product manufacturer Do not apply at an ambient temperature of less than +10°C or greater than +25°C. Relative humidity: 50 %. • Coverage: ± 10 m²/l. • Drying (data at +20°C and 50% relative humidity): <ul style="list-style-type: none"> - Dust-dry: 4 to 5 h. - Recoatable: 24 to 48 h. • Safety: Refer to the safety data sheet and the text given on the packaging, in accordance with the applicable legislation.

Priority to wood

Surface preparation

Use on wood whose usage, nature, quality, treatments and preparation comply with the applicable standards and DTU (DTU 59.1). The inspection and preparation of the surface are the responsibility of the user.

Recommendations before application

- The varnish used must be of the thick binder type (Linitop Vernis*).
- Shake well before use.
- Product ready to use.
- It is recommended doing a test beforehand on a small area.
- Avoid stacking the woodwork before it has completely dried.
- After opening the pot, it is advisable to use all of the product.
- Do not apply to wood treated with a water repellent beforehand.
- Not suitable for outdoor use.
- Do not apply to polished or sealed wood, or prepare beforehand to make the wood bare (see wood preparation).
- Complies with the applicable standards and DTU.
- The moisture of the wood before application must not be greater than 12%.

Surface preparation of the wood

According to the condition of the surface:

New wood:

- Degrease, sand and clean.
- Apply a coat of diluted Linitop Vernis*.

Old varnish (damaged coating):

- Sand, strip, scrape, brush, clean.
- The surface must be free of any finishing coat.
- Once the wood has been made bare, prepare the wood with a first coat of diluted Linitop Vernis*.

NB: This preparation is essential before applying Bouche-pores.

Directions for use

- Always prepare the wood with a first coat of diluted Linitop Vernis*.
- Apply a coat of Bouche-pores.
- Sand lightly after hardening, clean and finish with a finishing varnish.

Advice of the professionals

- Work in well ventilated rooms.
- Wear suitable protective equipment such as rubber gloves, a mask and glasses.

LINITOP® is a trademark



Durieu S.A.
91070 BONDOUFLE - France
 T. +33 (0)1 60 86 48 70
 F. +33 (0)1 60 86 84 84
 info@durieu.com
 www.durieu.com

Durieu Coatings S.A. / N.V.
New Tech Center
Avenue Albert Einstein 2 A
1348 Louvain-La-Neuve
Belgique / België
 T. +32 (0)10 420 090
 F. +32 (0)10 420 099
 info@durieucoatings.com
 www.durieucoatings.com

0800 95 549

For further help or advice please contact us on:
Belgium: +32 (0)10 420090 - 0800 95549
France: +33 (0)1 60 86 48 70
or consult our site: www.linitop.com

